

mNN

230.0
227.5
225.0
222.5
220.0
217.5
215.0
212.5

212.0

| WSP [mNN] | Q [m³/s] |
|-----------|----------|
| HQextrem | |
| 216.83 | 103.64 |
| HQ200 | |
| 216.73 | 81.43 |
| HQ100 | |
| 216.69 | 74.03 |
| HQ50 | |
| 216.67 | 71.11 |
| HQ25 | |
| 216.60 | 59.91 |
| HQ10 | |
| 216.49 | 49.88 |
| HQ5 | |
| 216.22 | 41.52 |
| MHQ | |
| 215.69 | 28.17 |
| 0,5*MHQ | |
| 215.01 | 14.09 |
| 0,1*MHQ | |
| 214.16 | 2.82 |

| Nicht abflusswirksam | | | | | | | | | | | | | | | | | |
|----------------------|-------------------|---------------|---------|---------|---------|---------|--------|--------|--------|----------------|--------|--------|--------|--------|--------|--------|--|
| Offenes Profil | Y (mNN) | 220.53 | 220.07 | 217.67 | 216.58 | 216.44 | 216.78 | 216.21 | 216.09 | 215.85 | 216.07 | 216.02 | 216.27 | 217.30 | 220.48 | 222.06 | |
| | X (m) | -233.27 | -219.24 | -190.19 | -131.09 | -109.05 | -97.03 | -75.99 | -23.90 | -10.30 | 18.26 | 94.10 | 125.04 | 139.01 | 158.96 | 173.93 | |
| | DVWK-Bewuchs | ax (m) | | | | | | | | | | | | | | | |
| | ay (m) | | | | | | | | | | | | | | | | |
| | dp (m) | | | | | | | | | | | | | | | | |
| | Rauheiten Ks (mm) | | | | | | | | | | | | | | | | |
| | Teilabschnitte | Vorland links | | | | | | | | Vorland rechts | | | | | | | |

Syre, Querprofile

Projekt: TIMIS flood / Dezember 2010

Profil-Nr. 190900
Modell-km 10.876
X-Maßstab 1 : 2500
Y-Maßstab 1 : 200
Gewässer-km AGE 10.876



Beauftragt durch

Bearbeitet durch

Ernst Basler + Partner
Hydrotec
Ingenieurgesellschaft für Wasser und Umwelt mbH